

Truly wireless

Ranger Pro



ATEX/IECEX Zone 0/CSA Class 1 Div 1



ISA100 & WirelessHART protocol



User-friendly and collaborative



Connected with System 1



Temp and triaxial capable



Specifications summary (See datasheet 125M5237 for full details)

Accelerometers	Axis	1 or 3 axes
	Amplitude range	±20 g peak
	Measurement accuracy	±5% (160 Hz) Z-axis, ±10% (160 Hz) X and Y axis
Static overall variables	Acceleration frequency range	Z axis: 5 Hz (±3dB) to 10 kHz (±3dB) 0.3–10kHz* X and Y axis: 5 Hz (±3dB) to 4 kHz (±3dB) (Tri-axial sensor only)
	Accel Fmin / Fmax (Hz)	2, 5, 10, 100, 200 / 200, 500, 1000, 2000, 5000, (10000 Z-axis only)
	Velocity range	5 – 2000 (Hz) / 0 – 50 mm/s (0 – 2 in/s)
	Velocity Fmin / Fmax (Hz)	5, 10 / 200, 500, 1000, 2000
	Measurement interval	10, 20, 30, 60, 120, 180, 240, 360 (minutes)
Waveforms and spectra	Accel Fmin / Fmax (Hz)	2, 5, 10 / 200, 500, 1000, 2000, 5000, 10000
	Number of samples	1024, 2048, 4096, 8192
	Velocity Fmin / Fmax (Hz)	5, 10 / 200, 500, 1000, 2000
	Number of lines	400, 800, 1600, 3200
	Waveform Measurement intervals	6, 8, 12, 24, 48, 168, 336, 672 (hours)
Temperature sensor	Measurement range	-40 °C to 120 °C (-40 °F to 248 °F) -40 °C to 125 °C (-40 °F to 257 °F)*
Wireless	Network standard	ISA100.11a or WirelessHART®
	Radio standard	IEEE 802.15.4, 2.45 GHz ISM band
	Encryption/ security	128-bit AES encrypted packets
	Wireless range	150 meters sensor to access point, 100 meters sensor to sensor, line of sight (actual range depends on obstacles present, gateway antenna type, and orientation of the sensor relative to the gateway antenna)
Battery and power	Type	Replaceable D size 3.6V lithium-thionyl chloride
	Life	Up to five years depending on the operating mode and configuration
Operating conditions	Operating temperature	-40 °C to 85 °C (-40 °F to 185 °F) -40 °C to 125 °C (-40 °F to 257 °F)*
Physical	Weight	230 grams (without battery; 300 grams with battery)
	Dimensions	Height: 88 mm; diameter: 40 mm
	Case material	316 stainless steel body and glass-reinforced, impact-resistant
	Mounting hole	M6 x 1mm X 5mm deep internal thread
	IP rating	IP67 dust and water resistant (pending)
Regulatory compliance	EMC conformity	IEC 61326-1, ETSI EN 301 489-1, CISPR22, ETSI EN 301 489-17
	Radio spectrum	ETSI EN 300 328
	Safety	ETSI EN 61010-1, IEC 62479
	Hazardous atmosphere	CSA Class I Division 1 Groups A, B, C, D T4 ATEX/IECEx Zone 0
	Conformity	Compliant with all CE and FCC/IC requirements
Compatible gateways	Bently Nevada	ISA100, up to 50 Ranger Pro sensors per gateway
	Emerson 1410S	1410S (compatible with firmware version 6.4.5 or newer) up to 200 Ranger Pro sensors per gateway
	Emerson 1410A/B/D	1410 (compatible with firmware version 4.7.84 or newer) up to 70 Ranger Pro sensors per gateway
	Emerson 1420	1420 (compatible with firmware version 4.7.84 or newer) up to 70 Ranger Pro sensors per gateway
	Honeywell	ISA100–Honeywell WDM R310.2-4 or higher, up to 40 Ranger Pro sensors per access point
	Yokogawa	ISA100–Yokogawa YFGW 410/510, up to 40 Ranger Pro sensors per access point
Tethered options	Tethered cable lengths	5, 10 Meter

* Denotes specification change with tethered option

Copyright 2021 Baker Hughes Company. All rights reserved. Baker Hughes provides this information on an "as is" basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information. The Baker Hughes logo, the Bently Nevada logo, and Ranger Pro are trademarks of Baker Hughes Company.

GEA34045A

(06/2021)



[bakerhughes.com](https://www.bakerhughes.com)